

Sale Engineering Products, manufacture a full range of compact lightweight, self - contained air compressors, designed to meet the specific needs of LPC requirements for dry pipe installations.

- Complies with LPC guidelines
- All materials supplied comply with the (PED) 97/23/EC regulations
- Pressure tested prior to despatch



Technical Specification:

- Electric motor driven single stage air compressor
- Outlet flexible hose connection: ½” BSPT
- Full electrical wiring and pressure testing
- Integrated wall brackets with anti vibration mounts
- Factory set pressure switch and restrictor
- Pressure safety relief valve (set at 5.5 Bar)
- Complimentary ½ Litre of ISO oil
- Starter, thermal overload and ‘on’ delay timer

On delay timer set at ten minutes to reduce the time required for water to reach an open head / test valve. The time delay also protects motor and pressure switch against hunting and overheating.

Dimensions: Width 600mm x Depth 310mm x Height 370mm (+ clearance for cooling / access)

Options:

- Floor Mounting Kit
- Riser Mounting Kit
- Pressure Gauge

Model	FAD (CFM)	Volts	Phase	Motor		Load	Pressure	
				HP	KW		Bar	PSI
SEP550S/LPC	5.7	240	1	1.5	1.1	6.5 amps	8	115
SEP550T/LPC	5.7	415	3	1.5	1.1	3.5 amps	8	115
SEP850S/LPC	8.0	240	1	2.5	1.8	8.5 amps	8	115
SEP850T/LPC	8.0	415	3	2.5	1.8	4.4 amps	8	115

Please note three phase compressors require a phase / neutral electrical supply. Please clearly state the application of the compressor at quotation stage or when ordering.